



HF-Selectalume II for TL5 lamps

HF-S 3/424 TL5 II 220-240V 50/60Hz

HF-Selectalume II TL5 is the most cost-effective, reliable and outstanding solution for fluorescent lamps. These ballasts are part of an overall high-efficiency lighting system that may help you or your customers to achieve any international or local energy code you need to comply with. HF-Selectalume II TL5 ballasts are the ideal choice for a broad range of new construction and retrofit applications within the commercial sector, including general surface mounting or office lighting, parking garages, warehouses, waterproof and other applications.

Product data

• General Information

Application Code	II
Type Version	mk1
Lamp Type	TL5
Number Of Lamps	3/4 piece/unit
Number Of Products On MCB (16A Type B) (Nom)	15
Automatic Restart	Yes

• Operating and Electrical

Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Operating Frequency (Nom)	45 kHz
Crestfactor (Nom)	1.7
Power Factor 100% Load (Nom)	0.98
Preheat Time	1.6 s
Mains Voltage	202-254V-8%+6%
Performance (AC)	
Mains Voltage Safety (AC)	198-264V-10%-+10%
Earth Leakage Current (Max)	0.5 mA
Inrush Current	0.35 ms
Width	
Ballast Factor (Nom)	1.11
Power Losses (Nom)	10.5/19 W
Inrush Current Peak (Max)	30 A

• Wiring

Connector Type	WAGO 744 connector
Input Terminals	

Cable Capacity	120 pF
Output Wires Mutual (Max)	
Connector Type	WAGO 744 connector [Suitable for manual wiring]
Output Terminals	
Cable Length Hot	0.75 m
Wiring	
Wire Striplength	8.0-9.0 mm
Dual Fixture Master/Slave	Possible, lamp wires 2m max. length [Master/Slave operation possible]
Input Terminal Cross Section	0.50-1.50 mm ²
Output Terminal Cross Section	0.50-1.50 mm ²
Cable Capacity Cold	120 pF
Output Wires - Earth (Max)	
Cable Capacity Hot	120 pF
Output Wires - Earth (Max)	

• System characteristics

Rated Ballast-Lamp Power	24 W
Rated Lamp Power On TL5	24 W
System Power On TL5	79.0/104.0 W
Lamp Power On TL5	68.5/85.0 W
Power Loss On TL5	10.5/19.0 W

• Temperature

T-Ambient (Max)	50 °C
T-Ambient (Min)	-15 °C
T-Storage (Max)	80 °C

PHILIPS

HF-Selectalume II for TL5 lamps

T-Storage (Min)	-40 °C
T-Case Lifetime (Nom)	75 °C
T-Case Maximum (Max)	75 °C

EMI 9 kHz ... 30 MHz	EN55015
Vibration Standard	IEC 68-2-6 Fc
Bumps Standard	IEC 68-2-29 Eb (10G/16ms)
Approval Marks	F-Marking

Mechanical and Housing

Housing	L 280x39x21.5
---------	---------------

Emergency Operation

Nominal Light Output After 60 Seconds	100% of EBLF
Normal Operating Voltage (DC)	220-240 V
Battery Voltage Guaranteed Operation	176-275 V
Battery Voltage Guaranteed Ignition	186-275 V
Emergency Ballast Lumen Factor (EBLF) (Nom)	0.7 %
Nominal Light Output After 5 Seconds	50% of EBLF

Hum And Noise Level	< 30 dB(A)
---------------------	------------

Product Data

Full product code	872790093937800
Order product name	HF-S 3/424 TL5 II 220-240V 50/60Hz
EAN/UPC - Product	8727900939378
Order code	93937800
Numerator -	1
Quantity Per Pack	10
Numerator - Packs per outer box	10
Material Nr. (12NC)	913713034666
Net Weight (Piece)	0.245 kg

Approval and Application

Energy Efficiency Index	A2
-------------------------	----

Photometric data

Ballast type	Lamp type	Lamp power	T _a = 40°C			T _a = 50°C			T _a = 60°C		
			T _c	84°C	97°C	X	T _c	84°C	97°C	X	T _c
HF-S 3/424 TL5 II 220-240V 50/60Hz	TL5 HO	3X24W	70,000 Hz	50,000 Hz	X	70,000 Hz	50,000 Hz	X	70,000 Hz	50,000 Hz	X
HF-S 3/424 TL5 II 220-240V 50/60Hz	TL5 HO	4X24W	70,000 Hz	50,000 Hz	X	70,000 Hz	50,000 Hz	X	70,000 Hz	50,000 Hz	X



© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 24
data subject to change